

Hard Surface Trim Guide

		(STYLE)	(DIMENSION: Inches)
		T-molding	94.5"x1.8"
		Reducer	94.5"x1.8"
		Flush Stair Nose	94.5"x4.3"
		End-Cap	94.5"x1.4"
		Quarter Round	94.5"x0.75"

		(STYLE)	(DIMENSION: Inches)
		T-molding	94.5"x1.7"
		Reducer	94.5"x1.7"
		Flush Stair	94.5"x2.8"
		End-Cap	94.5"x1.4"
		Quarter Round	94.5"x0.75"

Clip/track is included for T-molding, Reducer, End-Cap
 Coordinating moldings are waterproof



Color Coordinating Moldings

All transition pieces are vinyl wrapped and feature a waterproof plastic core with the exception of the quarter round which has a water resistant MDF core. The moldings are available in Reducer (RD), Endcap (EC), and Quarter Round (QR), T-mold (TH), and Flush Stairnose (FS). The Reducer, End Cap, and T-mold easily snap into the installation track (included). The T-mold and the Flush Stairnose do not come with an installation track and are intended to be installed using the recommended adhesive.

Description of Trims

Reducer: used to transition from hard surface floors to floors of different height.

End Cap or Square Nose: Used to transition from hard surface floors to carpet, masonry (fireplaces), sliding doors, and other exterior door jambs.

Quarter Round (Shoe Molding): Used to conceal the required expansion space between the wall and hard surface floors.

T-molding: Used to transition from hard surface floors to another floor that is the same height. T-moldings are also commonly used in doorways to join two different floating floors in adjoining rooms.

Flush Stairnose: Used to combine style and function, to enhance the beauty of a finished edge on a stair tread.

Reducer, End Cap, and T-molding Installation Instructions

1. Measure and cut the transition piece and installation track to fit.
2. Attach the track to the floor using adhesive, nails, or screws. (Depending on the thickness of the flooring, it may be necessary to add a shim under the track to raise the track and allow the trim to be installed correctly.)
3. Insert molding into the track working from one end to the other. Tap down with rubber mallet (if necessary).

Quarter Round Installation Instructions

1. Measure and trim to fit.
2. Attach the quarter round to the floor using finish nails or adhesive.

Flush Stairnose Installation Instructions

1. Measure and trim to fit.
2. Affix molding to floor using adhesive.
3. It is recommended to use an 8-10 inch band of adhesive or a few strips of double faced indoor/outdoor carpet tape in front of the Stairnose to keep the plank from moving away from the transition.

Adhesive: Engineered Floors recommends using Liquid Nails or a similar construction adhesive such as WF Taylor's Pinnacle (also recommended when installing planks on steps), or Hil-way Direct molding tape. It is available at www.1877floorguy.com or a similar tape. The adhesive manufacturer's recommendations must be followed completely.

Nails or Screws: Engineered Floors recommends using screws or nails with flat head to attach the molding track to the floor.

Finish Nails: When installing the Quarter Round using finish nails, the installer will need to use a nail set and putty the nail holes with appropriately colored wood putty available at most hardware stores.