



SPECIFICATION DATA

Style Name: Lux Haus II
Style Number: RR006
Thickness: 6.5mm
Wear Layer: 22 mil
Core Thickness: 5mm
Core Density: 1920
Attached Underlayment: 1.5 mm Cork
Embossing: EIR- Registered in Emboss
Surface Finish: Ceramic Bead
Nominal Dimensions: 5" x 36", 7" x 72", 9" x 72"
Actual Dimensions: 5" x 36", 7" x 72", 9" x 72"
Pattern Repeat: 7,5,4
Edge: Painted Bevel
Gloss Level: Matte
Traffic: Residential, Commercial
Antimicrobial: Yes
Locking Mechanism: 5G

PACKAGING

Pieces per carton: 8	Boxes per pallet: 75
Square feet per carton: 20.97	Square feet per pallet: 1,573
Weight per carton: 46.80 lbs	Weight per pallet: 3,565 lbs
	Pallet dimensions: 72.8" x 45.2" x 31.4"

TECHNICAL

IIC Sound Rating (ASTM E492): 70	STC Sound Rating (ASTM E90): 71
Residual Indentation (ASTM F1914): Passes	Static Load (ASTM F970): 500 psi (<.005")
Dininsional Stability (ASTM F2199): Passes	Chemical Resistance (ASTM F925): Passes
Resistance to heat (ASTM F1514): Passes	Resistance to light (ASTM F1515): Passes
Critical Radiant Flux (ASTM E648): Class 1	Optical Smoke Density (ASTM E662): <450
Slip Resistance (ASTM C1028): ADA compliant	FloorScore Certified: Yes

WARRANTY

Lifetime Residential *10 Year Commercial* Lifetime Waterproof & Pet